

## GdYWZWHc b

- \$)\$)~G977 \ YUj n1Xi mighYY`  
Y`YWfcd`UhYX`Zcf`W Uggjg`
- 8 Yg][ bYX`VmiH Y`cW UV`YXccf`cZZcbh  
dUbY`Zcf`dfchYW][b[ `h Y`gnghYa `gYW f][mi
- 8 Yg][ bYX`h Y`Ubh][j JVfU][cb`WUX`WUa d`  
hc`\_YYd`h Y`gnghYa `ghUV`Y`UbX`gUZym
- 5`i a ]bi a ` UbX`Yg`
- Gi ddcfh5H#5HL`Z`fa `a ch`Yf`VcUX`cf`  
% !g`chVUW\_d`UbY`



- **8 ]gd`Umff `(L`**
  - TFT LCD 6.4" (640x480)
  - High brightness.(300 nit)
  - High colors.(262,144)
  - Analog VGA input
  - Built-in 5 languages OSD.
  - LCD On/off switch.
- **8 ]gd`Umfi `(L`**
  - TFT LCD 8.4" (800x600)
  - High colors.(262,144)
  - Analog VGA input
  - Built-in 5 languages OSD.
  - LCD On/off switch.
- **8 ]gd`Umfi`L`**
  - TFT LCD 7" (800x480)
  - Analog VGA input
- **8 f]j Y6 Ung.`**
  - 1 x 3.5" FDD
  - 2 x 5.25" CD-ROM
  - 3 x 3.5" HDD
- **Dck Yf`gi dd`m`**
  - PS/2 ATX power supply (Optional)

- **7 cc`]b[ .**
  - Built-in two 8cm cooling fans
  - Power supply fan
- **CbY`\_YmVcUX`Wc`bbYWcf`]b`ZcbhidUbY`**
- **@8`bX]WUcf.** Power ON/OFF and Reset switches/ LED indicators at front panel
- **GdYU`\_Yf.`** 8 Ohm,0.4W 1.5"
- **7\ Uggjg`7 c`cfg.`**Black and beige color available, OEM color welcome
- **8 ]a Ybg]cb.`**
  - 483 (W) x 450 (D) x 177 (H) mm
  - N.W.: 13KGS, G.W.: 15KGS, CUFT: 3.3
- **CdYfU][b[ `HYa dYfUi fY.`**0° ~ 50° C
- **FYU][j Y`<i a ]X]m** 5~85%
- **C9A`GdYWZWHcb`K YWca Y`**
- **Cd]cb.`**
  - Power supply